

## Features

- 4x 13A UK shutter sockets with UK plug.
- 240 V
- Power on/off switch
- Power LED indicator
- Safety Thermal Cutoff
- 15m extension reel
- Easy wind handle
- Standards: BS EN 61242. ASTA Approved
- Maximum Load:  
720W/240V - Fully Wound  
3120W/240V - Fully Unwound

## RS PRO 15m 4 Socket Type G-British Cable Reel, 240V

RS Stock No.: 889-2488



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

- A robust extension lead has a wide base for free-standing, allowing for a neat and convenient cable management solution.
- With an integrated carry handle and a fifteen-metre cable length, the 4-gang extension allows maximum mobility around a mains power point. The ergonomic design features an easy-to-handle reel action to retract the cable after use.
- The four-socket extension lead has an integrated power switch with LED indicator, allowing more control over devices. It also has a thermal cut out which activates due to temperature rises caused by a power surge or overload, giving you peace of mind by minimising the risk of an electrical fire.
- Fixing points in the base allow the cable reel to be mounted for storage or while in use, for further versatility.

## General Specifications

|                    |                                        |
|--------------------|----------------------------------------|
| Type               | Case Reel                              |
| Cable Length       | 15 meters                              |
| Product Dimensions | H 22cm x W 20cm x D 17.2cm             |
| Socket             | 4x 13A UK shutter sockets with UK plug |

## Electrical Specifications

|              |                                                     |
|--------------|-----------------------------------------------------|
| Maximum Load | 720W/240V – Fully Wound; 3120W/240V – Fully Unwound |
| Cable Type   | PVC                                                 |
| Cable Size   | 1.25mm <sup>2</sup> (HO5VV-F)                       |
| Amp          | 13                                                  |
| Switch       | Double Pole                                         |

## Approvals

|               |                            |
|---------------|----------------------------|
| Declarations  | CE, REACH                  |
| Standards Met | BS EN 61242. ASTA Approved |

## Similar Products

| Stock No. | Brand  | Product Name               | Attribute 1        | Attribute 2 | Attribute 3            |
|-----------|--------|----------------------------|--------------------|-------------|------------------------|
| 889-2488  | RS PRO | CASE REEL                  | 15M extension Lead | 4 Sockets   | Type G - British       |
| 889-2490  | RS PRO | OPEN REEL                  | 25M extension Lead | 4 Sockets   | Type G - British       |
| 889-2494  | RS PRO | OPEN REEL                  | 25M extension Lead | 4 Sockets   | Type F - German Schuko |
| 889-2497  | RS PRO | CASE REEL                  | 15M extension Lead | 4 Sockets   | Type F - German Schuko |
| 889-2501  | RS PRO | HEAVY DUTY METAL OPEN REEL | 40M extension Lead | 4 Sockets   | Type G - British       |
| 889-2504  | RS PRO | OPEN REEL                  | 50M extension Lead | 4 Sockets   | Type G - British       |

Connection Diagrams / Assembly Diagrams / Illustrations / Accessories

